

BOLT FEEDER

AUTOMATIC • LOW NOISE



- Feeding capacity up to 30 bolts per minute
- Single or dual feeding
- Top cover for low noise and high protection
- Control cabinet allow future upgrades
- CE safety Norms



TECHNICAL DATA	SINGLE FEED	DUAL FEED
POWER SUPPLY / FREQUENCY	400 VAC / 110 VAC / 50-60HZ	
OPERATING POWER	24 Vdc	
CONSUMPTION	300 VA	350VA
FEEDING CAPACITY (BOLTS PER MINUTE)	26 TO 29	24 TO 30
CYCLE TIME	2 S	4 S
HOPPER CAPACITY	10 LITRES	
NOMINAL AIR PRESSURE	6 BAR	
FEEDING HEAD STROKE / MOUNTING ANGLE	156 MM / 30°	
BOLT IMPELER / SELECTOR	110 BAR	
BOLT TRANSPORT (TO FEEDING HEAD/ CENTERING DEVICE)	PNEUMATIC / MECHANIC	
NOISE LEVEL	72 DB	
EXTERNAL DIMENSIONS (H X W X L)	1400 X 507 X 560 MM	
WEIGH (WITHOUT FEEDING HEAD / FEEDING HEAD)	144,5 / 8,5 KG	149,5/8,5(X2)KG
FEEDING HEAD INTERCONNECTION LENGTH	3000 MM	3000 (X2) MM
FEEDING HEAD LENGTH	750 MM	750 (X2)MM

MANUFACTURERS & SUPPLIERS OF RESISTANCE WELDING PRODUCTS

